





Contents

LED Interior/Exterior Lighting


| EuroLED Interior Lamps | 82 |
|---------------------------------------|---------|
| EuroLED Downlights | 83 - 85 |
| LED Interior Strip Lamps | 86 - 87 |
| White LED Strip Lamps | 88 - 89 |
| DuraLED White LED Lamps | 90 - 92 |
| LED Downlights | 93 |
| Round Courtesy Lamps | 94 - 95 |
| Square Courtesy Lamps | 96 - 97 |
| Recess Mount Courtesy Lamps | 98 |
| DuraLED Flush Mount Courtesy Lamps | 99 |
| Step Courtesy Lamps | 101 |
| Low Profile Step Courtesy Lamps | 102 |
| Dural ED Surface Mount Courtesy Lamns | 103 |

EuroLED Interior Touch Lamps

White single LED interior lamps with touch switching. Multiple lamps can be switched externally. White/red version features night light and dimmer functions. White version features momentary ON/OFF switch control. No dimming.

















| | BLACK SHROUD | WHITE SHROUD | |
|-------------------|---|-----------------|-----------|
| Part Number | 2JA 959 950-011 | 2JA 959 950-021 | WHITE/RED |
| | 2JA 959 950-551 | 2JA 959 950-561 | WHITE |
| Mounting | Two hole surface mount with mounting bushes supplied. | | |
| Voltage | Multivolt for optimum brightness at input voltage from 9 to 33 volts. | | |
| Power Consumption | 4W | | |
| Protection | Reverse polarity and transient spike circuit protection. IP 6K6 (Protection against dust and high-pressure water jets) IP 6K7 (Protection against dust and temporary water immersion) | | |
| Cable Length | Pre-wired with 2.5m of sheathed multi-core cable. | | |
| Approval Markings | (€) 10R 04-2894 (€ | | |







2JA 959 950-011


2JA 959 950-551


2JA 959 950-561

EuroLED Interior Lamp

EuroLED single LED interior lamp with either white, warm white, green, blue, red or amber LED. Provides ultra long service life and is shock and vibration proof.















| | BLACK SHROUD | WHITE SHROUD | | | |
|-------------------|---|-----------------|------------|------------|--|
| | 2JA 959 820-501 | 2JA 959 820-551 | WHITE | CLEAR LENS | |
| | 2JA 959 820-311 | 2JA 959 820-331 | WARM WHITE | CLEAR LENS | |
| Part Number | 2JA 959 820-401 | 2JA 959 820-421 | GREEN | GREEN LENS | |
| | 2JA 959 820-701 | 2JA 959 820-721 | BLUE | BLUE LENS | |
| | 2JA 959 822-501 | 2JA 959 822-521 | AMBER | AMBER LENS | |
| | 2JA 959 821-501 | 2JA 959 821-521 | RED | RED LENS | |
| Mounting | Two hole surface mount with mounting bushes supplied. | | | | |
| Voltage | Multivolt for optimum brightness at input voltage from 9 to 33 volts. | | | | |
| Power Consumption | 4W | | | | |
| Protection | Reverse polarity and transient spike circuit protection. IP 6K6 (Protection against dust and high-pressure water jets) IP 6K7 (Protection against dust and temporary water immersion) | | | | |
| Cable Length | Pre-wired with 2.5m of sheathed multi-core cable. | | | | |
| Approval Markings | €4) 10R 04-2894 (€ | | | | |












2JA 959 820-311 2JA 959 820-401











| | WHITE PLASTIC RIM | POLISHED STAINLESS STEEL RIM | |
|-------------------|--|------------------------------|--------------------|
| Part Number | 2JA 980 630-001 | 2JA 980 630-011 | WHITE/RED |
| | 2JA 980 630-101 | 2JA 980 630-111 | WARM WHITE/ RED |
| Mounting | Recess mount, 124mm hole. | | |
| Voltage | Multivolt for optimum brightness at input voltage from 9 to 33 volts. | | |
| Power Consumption | 4W | | |
| Protection | Reverse polarity and spike protected. Sealed against dust and water ingress. | | |
| Cable Length | Pre-wired with 0.5m of sheathed multi-core cable. | | |
| Approval Markings | CE | | |

EuroLED Touch 150 Downlights - Dual Colour


Dual colour EuroLED touch lamps with dimming and momentary switch control. Touch the white pad for ON/OFF, hold finger on the pad to cycle through dimming levels.











| | WHITE PLASTIC RIM | POLISHED STAINLESS STEEL RIM | |
|-------------------|--|------------------------------|------------|
| Part Number | 2JA 980 630-501 | 2JA 980 630-511 | WHITE |
| | 2JA 980 630-601 | 2JA 980 630-611 | WARM WHITE |
| Mounting | Recess mount, 124mm hole. | | |
| Voltage | Multivolt for optimum brightness at input voltage from 9 to 33 volts. | | |
| Power Consumption | 4W | | |
| Protection | Reverse polarity and spike protected. Sealed against dust and water ingress. | | |
| Cable Length | Pre-wired with 0.5m of sheathed multi-core cable. | | |
| Approval Markings | ((| | |

EuroLED Touch 150 Downlights - Single Colour

Single colour EuroLED touch lamps with momentary switch control. Touch the white pad for ON, touch the black pad for OFF. No dimming.






2JA 980 630-601







| | 4 | | |
|-------------------|--|-----------------|------------|
| | WHITE PLASTIC RIM POLISHED STAINLESS STEEL RIM | | |
| Part Number | 2JA 980 631-501 | 2JA 980 631-511 | WHITE |
| | 2JA 980 631-601 | 2JA 980 631-611 | WARM WHITE |
| Mounting | Recess mount, 124mm hole. | | |
| Voltage | Multivolt for optimum brightness at input voltage from 9 to 33 volts. | | |
| Power Consumption | 4W | | |
| Protection | Reverse polarity and spike protected. Sealed against dust and water ingress. | | |
| Cable Length | Pre-wired with 0.5m of sheathed multi-core cable. | | |
| Approval Markings | (€ | | |

EuroLED 150 Downlights

Efficient, state-of-the art LED lamps offering advanced technology for durable and power saving interior and exterior installations. No switching or dimming.





2JA 980 631-601

EuroLED 115 Downlights

Round LED high intensity downlights offering class leading efficiency and durability. Supplied with white or polished stainless steel rims to suit.










2JA 980 820-101

Sealed cable entry 2JA 980 828-111









| | WHITE SPACER | | |
|-------------------|--|------------------------------|------------|
| Part Number | WHITE PLASTIC RIM | POLISHED STAINLESS STEEL RIM | |
| Part Number | 2JA 980 820-001 | 2JA 980 820-011 | WHITE |
| | 2JA 980 820-101 | 2JA 980 820-111 | WARM WHITE |
| | WHITE SPACER WITH SWITCH | | |
| Part Number | 2JA 980 828-001 | 2JA 980 828-011 | WHITE |
| | 2JA 980 828-101 | 2JA 980 828-111 | WARM WHITE |
| Mounting | Surface mount via spacer. Recess mount, 90mm hole. | | |
| Voltage | Multivolt for optimum brightness at input voltage from 10 to 33 volts. | | |
| Power Consumption | 4.5W | | |
| Protection | Reverse polarity and spike protected. Sealed against dust and water ingress. | | |
| Cable Length | Pre-wired with 0.5m of sheathed multi-core cable. | | |
| Approval Markings | (€ | | |

EuroLED 95 Downlights

Round LED high intensity downlights offering class leading efficiency and durability. Supplied with white or polished stainless steel rims to suit.






2JA 980 940-111



2JA 980 940-311











| | SCREW MOUNT | | |
|-------------------|--|------------------------------|------------|
| D (N) | WHITE PLASTIC RIM | POLISHED STAINLESS STEEL RIM | |
| Part Number | 2JA 980 940-001 | 2JA 980 940-011 | WHITE |
| | 2JA 980 940-101 | 2JA 980 940-111 | WARM WHITE |
| | SPRING CLIP MOUNT | | |
| Part Number | 2JA 980 940-201 | 2JA 980 940-211 | WHITE |
| | 2JA 980 940-301 | 2JA 980 940-311 | WARM WHITE |
| Mounting | Recess mount, 72mm hole. Screw or spring clip options. | | |
| Power Consumption | 4W | | |

Other specifications as per P/N 2JA 958 82x-xxx.



LED INTERIOR LIGHTING



| | SCREW MOUNT - 12 VOLT | | |
|-------------------|---|-------------------------------|------------|
| Part Number | WHITE PLASTIC RIM | POLISHED STAINLESS STEEL RIM | |
| | 2JA 958 110-011 | 2JA 958 110-021 | WHITE |
| | 2JA 958 109-011 | 2JA 958 109-021 | WARM WHITE |
| | SCREW MOUNT - 24 VOLT | | |
| Part Number | 2JA 958 110-111 | 2JA 958 110-121 | WHITE |
| | 2JA 958 109-111 | 2JA 958 109-121 | WARM WHITE |
| Mounting | Recess mount, 72mm hole. | | |
| Voltage | 12V DC or 24V DC | | |
| Power Consumption | <3W | | |
| Protection | IP 6K7 (Protection against dust and temporary water immersion) IP 6K9K (Protection against dust and high pressure/steam jet cleaning) | | |
| Cable Length | Pre-wired with 120mm of cable | Pre-wired with 120mm of cable | |
| Approval Markings | (€ | | |
| | - | | |

EuroLED 75 Downlights - Screw Mount

Round LED high intensity downlights offering class leading efficiency and durability. Supplied with white or polished stainless steel rims to suit.





2JA 958 109-021











| | SPRING CLIP MOUNT - 12 VOLT | | |
|-------------|-----------------------------|------------------------------|------------|
| D . N . I | WHITE PLASTIC RIM | POLISHED STAINLESS STEEL RIM | |
| Part Number | 2JA 958 110-511 | 2JA 958 110-521 | WHITE |
| | 2JA 958 109-511 | 2JA 958 109-521 | WARM WHITE |
| | SPRING CLIP MOUNT - 24 VOLT | | |
| Part Number | 2JA 958 110-611 | 2JA 958 110-621 | WHITE |
| | 2JA 958 109-611 | 2JA 958 109-621 | WARM WHITE |

Specifications as per P/N 2JA 958 1xx-xxx. Diagram shown.

EuroLED 75 Downlights - Spring Clip Mount


Round LED high intensity downlights offering class leading efficiency and durability. Supplied with white or polished stainless steel rims to suit.




ILLUMINATION CHARTS EuroLED 95 - Warm White EuroLED 75 - White 300 Lux _100 _ Lux 30 -- 30 Spread pattern H=30° V=30° Half centre value in luminous intensity Half centre value in luminous intensity

LED Interior/Exterior Awning Strip Lamp - Surface Mount - 15° Spread

LED awning lamp with an ultra slim profile of only 11mm, a heavy duty Grilamid® lens and low power consumption of less than 3W. It comes complete with white as well as charcoal end caps and can be accessorised with a matching 45° mounting bracket to angle the beam further. Combining state of the art technology with sophisticated looks, this new low profile LED Awning Lamp is a lighting solution which will find many applications. The precision optic, with a 15° downwards spread pattern, is designed to cause minimum glare.













| r nSafe | Lens Material | Power Supp |
|-------------|---------------|------------|
| ((E | PA | PASSIVI |
| | | |

| | 12 VOLT 24 VOLT | | |
|-------------------|--|----------------------|------------|
| Part Number | 2JA 980 879-011 | 2JA 980 879-111 | WHITE |
| | 2JA 980 879-201 | 2JA 980 879-301 | WARM WHITE |
| Mounting | Two hole surface mount. | | |
| Voltage | 12V DC or 24V DC | | |
| Power Consumption | <3W | | |
| Protection | Reverse polarity protection. IP 6K7 (Protection against dust and temporary water immersion) IP 6K9K (Protection against dust and high pressure/steam jet cleaning) | | |
| Cable Length | Pre-wired with 2.5m of of sheathe | ed multi-core cable. | |
| Spare Parts | 8HG 958 000-011 Mounting bracket 45° - White 8HG 958 000-021 Mounting bracket 45° - Charcoal 9HD 980 885-008 White screw caps 9HD 980 885-018 Charcoal screw caps 9HD 980 885-108 Chrome plated screw caps | | |



LED Interior/Exterior Strip Lamp - Surface Mount

These LED interior surface mount strip lamps feature a shallow 11mm profile, completely sealed housings and class leading efficiency. The range is ideal for a wide range of interior or exterior applications











| | 12 VOLT 24 VOLT | | |
|-------------------|--|---------------------|------------|
| Part Number | 2JA 958 124-001 | 2JA 958 124-401 | WHITE |
| | 2JA 958 124-101 | 2JA 958 124-501 | WARM WHITE |
| Mounting | Two hole surface mount. | | |
| Voltage | 12V DC or 24V DC | | |
| Power Consumption | <3W | | |
| Protection | Reverse polarity protection. IP 6K7 (Protection against dust and temporary water immersion) IP 6K9K (Protection against dust and high pressure/steam jet cleaning) | | |
| Cable Length | Pre-wired with 0.5m of of sheathe | d multi-core cable. | |











| | 12 VOLT | 24 VOLT | |
|-------------------|--|------------------------|---------------------|
| | 2JA 958 123-001 | 2JA 958 123-401 | WHITE |
| | 2JA 958 123-101 | 2JA 958 123-501 | WARM WHITE |
| Part Number | 2JA 958 121-011 | 2JA 958 121-411 | WHITE/BLUE |
| | 2JA 958 121-001 | 2JA 958 121-401 | WHITE/RED |
| | 2JA 958 121-111 | 2JA 958 121-511 | WARM WHITE/ BLUE |
| | 2JA 958 121-101 | 2JA 958 121-501 | WARM WHITE/ RED |
| Mounting | Surface mount. | | |
| Voltage | 12V DC or 24V DC | | |
| Power Consumption | White function: <3W | Colour function: <1W | |
| Protection | Reverse polarity protection. IP 6K7 (Protection against dust and temporary water immersion) IP 6K9K (Protection against dust and high pressure/steam jet cleaning) | | |
| Cable Length | Pre-wired with 0.5m of of sheathe | d multi-core cable. | |
| Spare Parts | 8HG 958 000-011 Mounti | ng bracket 45° - White | |

LED Interior/Exterior Strip Lamp with Sealed Switch - Surface Mount

These LED interior surface mount strip lamps with sealed waterproof switch feature a shallow 11mm profile, completely sealed housings and class leading efficiency. The range is ideal for a wide range of interior or exterior applications.





2JA 958 123-101 2JA 958 121-011 Warm White White/Blue



White/Red






2JA 958 121-101 Warm White/Red











| Part Number | 12 VOLT | 24 VOLT | |
|-------------|-----------------|-----------------|------------|
| | 2JA 980 881-012 | 2JA 980 881-112 | WHITE |
| | 2JA 980 881-212 | 2JA 980 881-312 | WARM WHITE |
| | 2JA 980 881-402 | 2JA 980 881-502 | BLUE |
| | 2JA 980 881-602 | 2JA 980 881-702 | RED |
| | 2JA 980 881-802 | 2JA 980 881-902 | GREEN |

Power Consumption <2W

ILLUMINATION CHART

Half centre value in luminous intensity

Other specifications as per P/N 2JA 958 124-001 on previous page.

LED Courtesy Strip Lamp - Surface Mount

These LED courtesy surface mount strip lamps feature a shallow 11mm profile, completely sealed housings and are available in white, warm white, blue, red & green colour variants.







White LED Interior Strip Lamp

High brightness white LED lamp with clear lens and attractive stainless steel cover. Stainless steel bezel features a unique internal tab lock for secure attachment and no visible fastenings.





Cable Length

2JA 980 681-111 Shown expanded

| 50 | 550 | Dimmab Analog DC I | |
|-------------------|---|------------------------------|------------|
| 6.0 | 26.5 | CommSafe (() Lens M | |
| | 12 VOLT | 24 VOLT | |
| Part Number | 2JA 980 681-011 | 2JA 980 681-511 | WHITE |
| Part Number | 2JA 980 681-111 | 2JA 980 681-611 | WARM WHITE |
| Mounting | Two hole recess mount. | | |
| Power Consumption | 2W | | |
| Protection | Reverse polarity protection. IP 6K7 (Protection against dust an | d temporary water immersion) | , |


IP 6K9K (Protection against dust and high pressure/steam jet cleaning)


Pre-wired with 2.5m of sheathed multi-core cable.

White LED Interior Strip Lamp

High brightness white LED lamp with clear lens. Ideal for steps, interior or exterior courtesy lighting and storage areas.









LED INTERIOR LIGHTING








| Part Number | 2JA 959 073-001 | 2JA 959 073-007 (Pack of 10) | 12 VOLT |
|-------------------|--|------------------------------|---------|
| Part Number | 2JA 959 073-201 | 2JA 959 073-207 (Pack of 10) | 24 VOLT |
| Mounting | Two hole recess mount. | | |
| Power Consumption | 2W | | |
| Protection | Reverse polarity protection. IP 6K7 (Protection against dust and temporary water immersion) IP 6K9K (Protection against dust and high pressure/steam jet cleaning) | | |
| Cable Length | Pre-wired with 2.5m of sheathed multi-core cable. | | |

| | See page 69 for red and blue colour va |
|--|--|
|--|--|

White LED Courtesy Strip Lamp

White LED interior strip lamp with clear lens. Ideal for steps, interior or exterior courtesy lighting and storage areas.






DuraLED 12 White LED Wide Spread Lamp - White Lens

White high brightness LED lamp. Exceptional light output, incorporating high efficacy LEDs. Low power consumption (3 watts) and low heat.












| Part Number | 2JA 959 700-102 | | |
|-------------------|--|--|--|
| Mounting | Two hole surface mount with mounting bushes supplied. | | |
| Voltage | Multivolt for optimum brightness in 12 and 24 volt systems. | | |
| Power Consumption | 3W | | |
| Protection | Reverse polarity and 5000 watt Transient Voltage Suppressor (TVS). Sealed against dust and water ingress. | | |
| Cable Length | Pre-wired with 0.5m of sheathed multi-core cable. | | |
| Approval Markings | €4) 10R 04-2743 (€ | | |

DuraLED 20 White LED Wide Spread Lamp - White Lens

White high brightness LED lamp with exceptional light output. Incorporates high efficacy electronics and LEDs resulting in low power consumption (<4 watts) and low heat. The lamp is fully sealed against dust and moisture ingress.











| Part Number | 2JA 980 608-011 |
|-------------------|--|
| Mounting | Two hole surface mount with mounting bushes supplied. |
| Voltage | Multivolt for optimum brightness at input voltage from 9 to 33 volts. |
| Power Consumption | <4W |
| Protection | Reverse polarity and spike protected. IP 6K6 (Protection against dust and high pressure water jets) IP 6K7 (Protection against dust and temporary water immersion) |
| Cable Length | Pre-wired with 2.5m of sheathed multi-core cable. |
| Approval Markings | (€ |











| Dura | LED 36 | White | LED | Lamp |
|------|--------|-------|-----|------|
| | | | | |

White LED interior lamp with either a diffusion or clear acrylic lens. The lamps are shock and vibration proof and are fully sealed against dust and moisture ingress.





2JA 959 037-501

| Part Number | CLEAR LENS DIFFUSION LENS | | |
|-------------------|--|------------------------------|--|
| Part Number | 2JA 959 037-511 | 2JA 959 037-501 | |
| Mounting | Two hole surface mount with mounting bu | ushes supplied. | |
| Voltage | Multivolt for optimum brightness at input | voltages from 9 to 33 volts. | |
| Power Consumption | 4W | | |
| Protection | Reverse polarity and 5000 watt Transient Voltage Suppressor (TVS) IP 6K6 (Protection against dust and high pressure water jets) IP 6K7 (Protection against dust and temporary water immersion) | | |
| Cable Length | Pre-wired with 2.5m of sheathed multi-core cable. | | |
| Approval Markings | €4 10R 04-2893 (€ | | |



Approval Markings

(E4) 10R 04-2893



| | WHITE LENS CHARCOAL LENS | | |
|-------------------|--|--------------------------------------|--------|
| Don't Novel or | 2JA 959 037-201 | 2JA 959 037-211 | SPREAD |
| Part Number | 2JA 959 037-401 | 2JA 959 037-411 | NARROW |
| | 2JA 959 037-301 | 2JA 959 037-311 | PENCIL |
| Mounting | Two hole surface mount with mounting bushes supplied. | | |
| Voltage | Multivolt for optimum brightness a | t input voltages from 9 to 33 volts. | |
| Power Consumption | <9W | | |
| Protection | Reverse polarity and spike protected. IP 6K6 (Protection against dust and high pressure water jets) IP 6K7 (Protection against dust and temporary water immersion) | | |
| Cable Length | Pre-wired with 2.5m of sheathed m | nulti-core cable. | |

(€


DuraLED 36 White LED Lamp

White high brightness LED lamp with clear Grilamid® lens. Incorporates high efficacy electronics and LEDs resulting in low power consumption (<9 watts) and low heat. Lens manufactured from Grilamid® clear nylon which features high UV and chemical resistance, and high impact strength. The lamp is fully sealed against dust and moisture ingress.





2JA 959 037-211




DuraLED Combi-S 50 White LED Lamp - White Lens

White high brightness LED lamp with clear and exceptional light output. Incorporates high efficacy electronics and LEDs resulting in low power consumption (<12 watts) and low heat. Spread light is suitable for general area lighting. The lamp is fully sealed against dust and moisture ingress.





2JA 980 629-001









| Part Number | 2JA 980 629-501 WIDE | |
|-------------------|--|--------|
| Part Number | 2JA 980 629-001 | SPREAD |
| Mounting | Two hole surface mount with mounting bushes supplied. | |
| Voltage | Multivolt for optimum brightness at input voltages from 9 to 33 volt | S. |
| Power Consumption | <12W | |
| Protection | Reverse polarity and transient spike circuit protection. IP 6K7 (Protection against dust and temporary water immersion) IP 6K9K (Protection against dust and high pressure/steam jet clean | ning) |
| Cable Length | Pre-wired with 2.5m of sheathed multi-core cable. | |
| Approval Markings | (€ | |



Ultra slim height of only 25mm.

DuraLED Combi-S 50 White LED Lamp - Charcoal Lens

White high brightness LED lamp with clear Grilamid® lens. Incorporates high efficacy electronics and LEDs resulting in low power consumption (<12 watts) and low heat. Lens manufactured from Grilamid® clear nylon which features high UV and chemical resistance, and high impact strength. The lamp is fully sealed against dust and moisture ingress.








| Part Number | 2JA 980 604-031 | WIDE SPREAD |
|--|---|-------------|
| Mounting | Two hole surface mount with mounting bushes supplied. | |
| Voltage | Multivolt for optimum brightness at input voltages from 9 to 33 volt | S. |
| Power Consumption | <12W | |
| Protection | Protection Reverse polarity and transient spike circuit protection. IP 6K7 (Protection against dust and temporary water immersion) IP 6K9K (Protection against dust and high pressure/steam jet cleaning) | |
| Cable Length Pre-wired with 2.5m of sheathed multi-core cable. | | |
| Approval Markings | (€ | |



Ultra slim height of only 25mm.



LED INTERIOR LIGHTING











LED Downlights - Round

Round LED downlights offering class leading efficiency and durability. Supplied with white rims to suit




| | 12 VOLT | 24 VOLT | |
|--|--|-----------------|------------|
| Part Number | 2JA 959 599-002 | 2JA 959 599-102 | WHITE |
| | 2JA 959 596-002 | 2JA 959 596-102 | WARM WHITE |
| Mounting | Recess mount, 50mm diameter hole. | | |
| Power Consumption | 1W | | |
| Protection | Reverse polarity and voltage spike protection. Fully sealed against dust, high-pressure washing and temporary water immersion. | | |
| Cable Length | Pre-wired with 120mm of cable. | | |
| See page 112 for additional rim colours. | | | |












LED Downlights - SquareSquare LED downlights offering class leading

square LED downlights offering class leading efficiency and durability. Supplied with white rims to suit.



| | 12 VOLT 24 VOLT | | |
|--|--|-----------------|------------|
| Part Number | 2JA 980 596-002 | 2JA 980 596-102 | WHITE |
| | 2JA 980 597-002 | 2JA 980 597-102 | WARM WHITE |
| Mounting | Recess mount, 50mm diameter hole. | | |
| Power Consumption | 1W | | |
| Protection | Reverse polarity protection. Fully sealed against dust, high-pressure washing and temporary water immersion. | | |
| Cable Length | Pre-wired with 120mm of cable. | | |
| See page 112 for additional rim colours. | | | |




Round Courtesy Lamps

- Clear Lens

Attractive, energy efficient round LED courtesy lamps for interior and exterior use. Available in nine exciting colours with a range of different rim finishes.















| ROUND COURTESY LAMPS - CLEAR LENS | | |
|--|--|--|
| Mounting Recess mount, 50mm diameter hole. | | |
| Power Consumption | <1W | |
| Protection | Reverse polarity and voltage spike protection. Fully sealed against dust, high-pressure washing and temporary water immersion. | |
| Cable Length Pre-wired with 120mm of cable. | | |
| Pack Size 24 lamps | | |
| See page 112 for spare parts and surface mount housings. | | |



| | 12V DC | 24V DC | |
|-----|-----------------|-----------------|---|
| | 2XT 980 500-097 | 2XT 980 501-097 | SATIN CHROME PLATED STAINLESS STEEL RIM |
| Ë | 2XT 980 500-027 | 2XT 980 501-027 | POLISHED STAINLESS STEEL RIM |
| M W | 2XT 980 500-037 | 2XT 980 501-037 | GOLD PLATED STAINLESS STEEL RIM |
| | 2XT 980 500-047 | 2XT 980 501-047 | WHITE PLASTIC RIM |
| | 2XT 980 500-057 | 2XT 980 501-057 | BLACK PLASTIC RIM |



| ESS | 12V DC | 24V DC | |
|------|-----------------|-----------------|---|
| H | 2XT 980 500-597 | 2XT 980 501-597 | SATIN CHROME PLATED STAINLESS STEEL RIM |
| HTE | 2XT 980 500-527 | 2XT 980 501-527 | POLISHED STAINLESS STEEL RIM |
| WH | 2XT 980 500-537 | 2XT 980 501-537 | GOLD PLATED STAINLESS STEEL RIM |
| NHAN | 2XT 980 500-547 | 2XT 980 501-547 | WHITE PLASTIC RIM |
| ш | 2XT 980 500-557 | 2XT 980 501-557 | BLACK PLASTIC RIM |



| | 12V DC | 24V DC | |
|------|-----------------|-----------------|---|
| 벁 | 2XT 980 500-297 | 2XT 980 501-297 | SATIN CHROME PLATED STAINLESS STEEL RIM |
| WH | 2XT 980 500-227 | 2XT 980 501-227 | POLISHED STAINLESS STEEL RIM |
| WARM | 2XT 980 500-237 | 2XT 980 501-237 | GOLD PLATED STAINLESS STEEL RIM |
| 3 | 2XT 980 500-247 | 2XT 980 501-247 | WHITE PLASTIC RIM |
| | 2XT 980 500-257 | 2XT 980 501-257 | BLACK PLASTIC RIM |



| SS | 12V DC | 24V DC | |
|---------------|-----------------|-----------------|---|
| ITE HTNESS | 2XT 980 500-797 | 2XT 980 501-797 | SATIN CHROME PLATED STAINLESS STEEL RIM |
| WH | 2XT 980 500-727 | 2XT 980 501-727 | POLISHED STAINLESS STEEL RIM |
| ARM | 2XT 980 500-737 | 2XT 980 501-737 | GOLD PLATED STAINLESS STEEL RIM |
| MHAN | 2XT 980 500-747 | 2XT 980 501-747 | WHITE PLASTIC RIM |
| ū | 2XT 980 500-757 | 2XT 980 501-757 | BLACK PLASTIC RIM |

| | 12V DC | 24V DC | |
|----|-----------------|-----------------|---|
| | 2XT 980 502-097 | 2XT 980 503-097 | SATIN CHROME PLATED STAINLESS STEEL RIM |
| H | 2XT 980 502-027 | 2XT 980 503-027 | POLISHED STAINLESS STEEL RIM |
| GR | 2XT 980 502-037 | 2XT 980 503-037 | GOLD PLATED STAINLESS STEEL RIM |
| | 2XT 980 502-047 | 2XT 980 503-047 | WHITE PLASTIC RIM |
| | 2XT 980 502-057 | 2XT 980 503-057 | BLACK PLASTIC RIM |



| | 12V DC | 24V DC | |
|----|-----------------|-----------------|---|
| | 2XT 980 502-297 | 2XT 980 503-297 | SATIN CHROME PLATED STAINLESS STEEL RIM |
| J. | 2XT 980 502-227 | 2XT 980 503-227 | POLISHED STAINLESS STEEL RIM |
| В | 2XT 980 502-237 | 2XT 980 503-237 | GOLD PLATED STAINLESS STEEL RIM |
| | 2XT 980 502-247 | 2XT 980 503-247 | WHITE PLASTIC RIM |
| | 2XT 980 502-257 | 2XT 980 503-257 | BLACK PLASTIC RIM |



| | 12V DC | 24V DC | |
|----|-----------------|-----------------|---|
| | 2XT 980 502-497 | 2XT 980 503-497 | SATIN CHROME PLATED STAINLESS STEEL RIM |
| AN | 2XT 980 502-427 | 2XT 980 503-427 | POLISHED STAINLESS STEEL RIM |
| Շ | 2XT 980 502-437 | 2XT 980 503-437 | GOLD PLATED STAINLESS STEEL RIM |
| | 2XT 980 502-447 | 2XT 980 503-447 | WHITE PLASTIC RIM |
| | 2XT 980 502-457 | 2XT 980 503-457 | BLACK PLASTIC RIM |



| | 12V DC | 24V DC | |
|-----|-----------------|-----------------|---|
| | 2XT 980 507-097 | 2XT 980 508-097 | SATIN CHROME PLATED STAINLESS STEEL RIM |
| BER | 2XT 980 507-027 | 2XT 980 508-027 | POLISHED STAINLESS STEEL RIM |
| Α | 2XT 980 507-037 | 2XT 980 508-037 | GOLD PLATED STAINLESS STEEL RIM |
| | 2XT 980 507-047 | 2XT 980 508-047 | WHITE PLASTIC RIM |
| | 2XT 980 507-057 | 2XT 980 508-057 | BLACK PLASTIC RIM |



| | 12V DC | 24V DC | |
|----------|-----------------|-----------------|---|
| | 2XT 980 507-307 | 2XT 980 508-297 | SATIN CHROME PLATED STAINLESS STEEL RIM |
| RED | 2XT 980 507-227 | 2XT 980 508-227 | POLISHED STAINLESS STEEL RIM |
| <u>~</u> | 2XT 980 507-237 | 2XT 980 508-237 | GOLD PLATED STAINLESS STEEL RIM |
| | 2XT 980 507-247 | 2XT 980 508-247 | WHITE PLASTIC RIM |
| | 2XT 980 507-257 | 2XT 980 508-257 | BLACK PLASTIC RIM |



| ٥ | 12V DC | 24V DC | |
|-------|-----------------|-----------------|---|
| | 2XT 980 507-497 | 2XT 980 508-497 | SATIN CHROME PLATED STAINLESS STEEL RIM |
| P REI | 2XT 980 507-427 | 2XT 980 508-427 | POLISHED STAINLESS STEEL RIM |
| DEEP | 2XT 980 507-437 | 2XT 980 508-437 | GOLD PLATED STAINLESS STEEL RIM |
| | 2XT 980 507-447 | 2XT 980 508-447 | WHITE PLASTIC RIM |
| | 2XT 980 507-457 | 2XT 980 508-457 | BLACK PLASTIC RIM |



| ORANGE | 12V DC | 24V DC | |
|--------|-----------------|-----------------|---|
| | 2XT 980 507-697 | 2XT 980 508-697 | SATIN CHROME PLATED STAINLESS STEEL RIM |
| | 2XT 980 507-627 | 2XT 980 508-627 | POLISHED STAINLESS STEEL RIM |
| ORA | 2XT 980 507-637 | 2XT 980 508-637 | GOLD PLATED STAINLESS STEEL RIM |
| | 2XT 980 507-647 | 2XT 980 508-647 | WHITE PLASTIC RIM |
| | 2XT 980 507-657 | 2XT 980 508-657 | BLACK PLASTIC RIM |




Square Courtesy Lamps

- Clear Lens

Attractive, energy efficient square LED courtesy lamps for interior and exterior use. Available in nine exciting colours with a range of different rim finishes.













| SQUARE COURTESY LAMPS - CLEAR LENS | | | |
|------------------------------------|--|--|--|
| Mounting | Recess mount, 50mm diameter hole. | | |
| Power Consumption | <1W | | |
| Protection | Reverse polarity and voltage spike protection. Fully sealed against dust, high-pressure washing and temporary water immersion. | | |
| Cable Length | Pre-wired with 120mm of cable. | | |
| Pack Size | 24 lamps | | |

See page 112 for spare parts and surface mount housings.










| | 12V DC | 24V DC | |
|---|-----------------|-----------------|-------------------------|
| | 2XT 980 580-067 | 2XT 980 581-067 | SATIN CHROME PLATED RIM |
| Ë | 2XT 980 580-077 | 2XT 980 581-077 | CHROME PLATED RIM |
| × | 2XT 980 580-037 | 2XT 980 581-037 | GOLD PLATED RIM |
| | 2XT 980 580-057 | 2XT 980 581-057 | WHITE PLASTIC RIM |
| | 2XT 980 580-047 | 2XT 980 581-047 | BLACK PLASTIC RIM |

| NESS | 12V DC | 24V DC | |
|------|-----------------|-----------------|-------------------------|
| 뿔 | 2XT 980 580-567 | 2XT 980 581-567 | SATIN CHROME PLATED RIM |
| ITE | 2XT 980 580-577 | 2XT 980 581-577 | CHROME PLATED RIM |
| ĭe w | 2XT 980 580-537 | 2XT 980 581-537 | GOLD PLATED RIM |
| HAN | 2XT 980 580-557 | 2XT 980 581-557 | WHITE PLASTIC RIM |
| | 2XT 980 580-547 | 2XT 980 581-547 | BLACK PLASTIC RIM |

| WARM WHITE | 12V DC | 24V DC | |
|------------|-----------------|-----------------|-------------------------|
| | 2XT 980 580-267 | 2XT 980 581-267 | SATIN CHROME PLATED RIM |
| | 2XT 980 580-277 | 2XT 980 581-277 | CHROME PLATED RIM |
| | 2XT 980 580-237 | 2XT 980 581-237 | GOLD PLATED RIM |
| | 2XT 980 580-257 | 2XT 980 581-257 | WHITE PLASTIC RIM |
| | 2XT 980 580-247 | 2XT 980 581-247 | BLACK PLASTIC RIM |

| WARM WHITE | 12V DC | 24V DC | |
|------------|-----------------|-----------------|-------------------------|
| | 2XT 980 580-767 | 2XT 980 581-767 | SATIN CHROME PLATED RIM |
| | 2XT 980 580-777 | 2XT 980 581-777 | CHROME PLATED RIM |
| | 2XT 980 580-737 | 2XT 980 581-737 | GOLD PLATED RIM |
| | 2XT 980 580-757 | 2XT 980 581-757 | WHITE PLASTIC RIM |
| ä | 2XT 980 580-747 | 2XT 980 581-747 | BLACK PLASTIC RIM |

| | 12V DC | 24V DC | |
|-----|-----------------|-----------------|-------------------------|
| | 2XT 980 582-097 | 2XT 980 583-097 | SATIN CHROME PLATED RIM |
| Z | 2XT 980 582-027 | 2XT 980 583-027 | CHROME PLATED RIM |
| GRE | 2XT 980 582-037 | 2XT 980 583-037 | GOLD PLATED RIM |
| | 2XT 980 582-057 | 2XT 980 583-057 | WHITE PLASTIC RIM |
| | 2XT 980 582-047 | 2XT 980 583-047 | BLACK PLASTIC RIM |




| | 12V DC | 24V DC | |
|----|-----------------|-----------------|-------------------------|
| | 2XT 980 582-297 | 2XT 980 583-297 | SATIN CHROME PLATED RIM |
| H. | 2XT 980 582-277 | 2XT 980 583-277 | CHROME PLATED RIM |
| В | 2XT 980 582-237 | 2XT 980 583-237 | GOLD PLATED RIM |
| | 2XT 980 582-257 | 2XT 980 583-257 | WHITE PLASTIC RIM |
| | 2XT 980 582-247 | 2XT 980 583-247 | BLACK PLASTIC RIM |



| | 12V DC | 24V DC | |
|-----|-----------------|-----------------|-------------------------|
| | 2XT 980 582-467 | 2XT 980 583-467 | SATIN CHROME PLATED RIM |
| ΥAΝ | 2XT 980 582-477 | 2XT 980 583-477 | CHROME PLATED RIM |
| ζ | 2XT 980 582-437 | 2XT 980 583-437 | GOLD PLATED RIM |
| | 2XT 980 582-457 | 2XT 980 583-457 | WHITE PLASTIC RIM |
| | 2XT 980 582-447 | 2XT 980 583-447 | BLACK PLASTIC RIM |



| | 12V DC | 24V DC | |
|-----|-----------------|-----------------|-------------------------|
| | 2XT 980 587-067 | 2XT 980 588-067 | SATIN CHROME PLATED RIM |
| BER | 2XT 980 587-077 | 2XT 980 588-077 | CHROME PLATED RIM |
| A | 2XT 980 587-037 | 2XT 980 588-037 | GOLD PLATED RIM |
| | 2XT 980 587-057 | 2XT 980 588-057 | WHITE PLASTIC RIM |
| | 2XT 980 587-047 | 2XT 980 588-047 | BLACK PLASTIC RIM |



| | 12V DC | 24V DC | |
|----|-----------------|-----------------|-------------------------|
| | 2XT 980 587-267 | 2XT 980 588-267 | SATIN CHROME PLATED RIM |
| ED | 2XT 980 587-277 | 2XT 980 588-277 | CHROME PLATED RIM |
| RE | 2XT 980 587-237 | 2XT 980 588-237 | GOLD PLATED RIM |
| | 2XT 980 587-257 | 2XT 980 588-257 | WHITE PLASTIC RIM |
| | 2XT 980 587-247 | 2XT 980 588-247 | BLACK PLASTIC RIM |



| | 12V DC | 24V DC | |
|-------|-----------------|-----------------|-------------------------|
| ۵ | 2XT 980 587-467 | 2XT 980 588-467 | SATIN CHROME PLATED RIM |
| P REI | 2XT 980 587-477 | 2XT 980 588-477 | CHROME PLATED RIM |
| DEEP | 2XT 980 587-437 | 2XT 980 588-437 | GOLD PLATED RIM |
| | 2XT 980 587-457 | 2XT 980 588-457 | WHITE PLASTIC RIM |
| | 2XT 980 587-447 | 2XT 980 588-447 | BLACK PLASTIC RIM |




| 12V DC | 24V DC | |
|-----------------|--|---|
| 2XT 980 587-667 | 2XT 980 588-667 | SATIN CHROME PLATED RIM |
| 2XT 980 587-677 | 2XT 980 588-677 | CHROME PLATED RIM |
| 2XT 980 587-637 | 2XT 980 588-637 | GOLD PLATED RIM |
| 2XT 980 587-657 | 2XT 980 588-657 | WHITE PLASTIC RIM |
| 2XT 980 587-647 | 2XT 980 588-647 | BLACK PLASTIC RIM |
| | 2XT 980 587-667 2XT 980 587-677 2XT 980 587-637 2XT 980 587-657 | 2XT 980 587-667 2XT 980 588-667 2XT 980 587-677 2XT 980 588-677 2XT 980 587-637 2XT 980 588-637 2XT 980 587-657 2XT 980 588-657 |



Narrow Rim Rectangular Courtesy Lamp

Narrow rim recess mount courtesy lamp with either white, warm white, green, blue, amber or red LEDs. Pack of 36 lamps.











| | 12 VOLT / 24 VOLT | | |
|-------------|-------------------|------------|------------|
| | 2XT 959 510-457 | WHITE | |
| Part Number | 2XT 959 510-937 | WARM WHITE | CLEAR LENS |
| | 2XT 959 510-157 | GREEN | CLEAR LENS |
| | 2XT 959 510-257 | BLUE | |










| | | Anatog De Input | | PASSIVE |
|---|--|-----------------|-------|------------|
| | 12 VOLT | 24 VOLT | | |
| | 2XT 959 510-007 | 2XT 959 510-057 | AMBER | CLEAR LENS |
| Part Number | 2XT 959 510-017 | 2XT 959 510-067 | AMBER | AMBER LENS |
| | 2XT 959 510-307 | 2XT 959 510-357 | RED | CLEAR LENS |
| | 2XT 959 510-317 | 2XT 959 510-337 | | RED LENS |
| Mounting | Mounting Two hole recess mount. | | | |
| Power Consumption | <1W | | | |
| Protection | Protection Reverse polarity protection. IP 6K6 (Protection against dust and high pressure water jets) IP 6K7 (Protection against dust and temporary water immersion) | | | |
| Cable Length | Pre-wired with 120mm of cable. | | | |
| Approval Markings | pproval Markings €4 10R 04-2906 (€ | | | |
| Approval markings are only applicable for Multivolt versions. | | | | |

Wide Rim Rectangular Courtesy Lamp

Wide rim recess mount courtesy lamp with either white, warm white, green, blue, amber or red LEDs. Pack of 36 lamps.











| | 12 VOLT / 24 VOLT | | |
|-------------|-------------------|------------|------------|
| | 2XT 959 510-427 | WHITE | |
| Part Number | 2XT 959 510-907 | WARM WHITE | CLEAR LENS |
| | 2XT 959 510-627 | GREEN | CLEAR LENS |
| | 2XT 959 510-657 | BLUE | |










| | 12 VOLT | 24 VOLT | | |
|---|--|-----------------|-------|------------|
| | 2XT 959 510-507 | 2XT 959 510-557 | AMBER | CLEAR LENS |
| Part Number | 2XT 959 510-517 | 2XT 959 510-567 | AMBER | AMBER LENS |
| | 2XT 959 510-707 | 2XT 959 510-757 | RED | CLEAR LENS |
| | 2XT 959 510-717 | 2XT 959 510-767 | KED | RED LENS |
| Mounting | ounting Two hole recess mount. | | | |
| Power Consumption | <1W | | | |
| Protection | Protection Reverse polarity protection. IP 6K6 (Protection against dust and high pressure water jets) IP 6K7 (Protection against dust and temporary water immersion) | | | |
| Cable Length | Pre-wired with 120mm of cable. | | | |
| Approval Markings | proval Markings (4) 10R 04-2906 (6 | | | |
| Approval markings are only applicable for Multivolt versions. | | | | |










| | 2XT 980 855-117 | WHITE | |
|-------------------|--|------------|--|
| | 2XT 980 855-167 | WARM WHITE | |
| Dant Nameh an | 2XT 980 855-267 | AMBER | |
| Part Number | 2XT 980 855-347 | RED | |
| | 2XT 980 855-417 | BLUE | |
| | 2XT 980 855-517 | GREEN | |
| Mounting | ting Two hole surface mount. | | |
| Voltage | Multivolt for optimum brightness in 12 and 24 volt systems. | | |
| Power Consumption | <0.5W | | |
| Protection | Reverse polarity protection. IP 6K7 (Protection against dust and temporary water immersion) IP 6K9K (Protection against dust and high-pressure/steam jet cleaning) | | |
| Cable Length | Pre-wired with 0.5m of sheathed multi-core cable. | | |
| Pack Size | 16 lamps | | |
| Approval Markings | (€ | | |

DuraLED Flush Mount Courtesy Lamp - Low Profile

These LED courtesy lamps feature a shallow 9mm profile and completely sealed housing. Available in a range of colours. Optic appears clear until illuminated.





P/N 2XT 980 855-167 P/N 2XT 980 855-267






P/N 2XT 980 855-517



HELLA LED Luminaires provide superior quality lighting solutions for Interior/Exterior lighting.
















Wide Rim Rectangular - Step Courtesy Lamp

Flush mount step lamp with either white, warm white, green, blue or red LEDs.

WIDE RIM RECTANGULAR - STEP COURTESY LAMP

| Mounting | Two hole recess mount. | |
|-------------------|---|--|
| Voltage | Multivolt for optimum brightness at input voltage from 8 to 28 volts (red lamps), or between 10 to 33 volts (blue, green, white and warm white lamps). | |
| Power Consumption | <1W | |
| Protection | Reverse polarity protection. IP 6K6 (Protection against dust and high pressure water jets) IP 6K7 (Protection against dust and temporary water immersion) | |
| Pack Size | 24 lamps | |
| Approval Markings | €4 10R 04-2906 (€ | |

| ш | Clear Lens | | |
|------|-----------------|---|--|
| | 2XT 959 680-807 | LAMP ONLY | |
| YHIT | 2XT 959 680-817 | POLISHED STAINLESS STEEL RIM | |
| | 2XT 959 680-847 | GOLD PLATED STAINLESS STEEL RIM | |
| | 2XT 959 680-857 | SATIN CHROME PLATED STAINLESS STEEL RIM | |



| HITE | Clear Lens | | |
|------|------------|-----------------|---|
| | Е | 2XT 959 680-407 | LAMP ONLY |
| | ≶ ∑ | 2XT 959 680-417 | POLISHED STAINLESS STEEL RIM |
| | WAR | 2XT 959 680-427 | GOLD PLATED STAINLESS STEEL RIM |
| | | 2XT 959 680-437 | SATIN CHROME PLATED STAINLESS STEEL RIM |



| | Clear Lens | |
|-----|-----------------|---|
| z | 2XT 959 680-907 | LAMP ONLY |
| REE | 2XT 959 680-917 | POLISHED STAINLESS STEEL RIM |
| O | 2XT 959 680-927 | GOLD PLATED STAINLESS STEEL RIM |
| | 2XT 959 680-937 | SATIN CHROME PLATED STAINLESS STEEL RIM |



| | Clear Lens | | |
|------|-----------------|---|--|
| ш | 2XT 959 680-607 | LAMP ONLY | |
| BLUE | 2XT 959 680-617 | POLISHED STAINLESS STEEL RIM | |
| | 2XT 959 680-627 | GOLD PLATED STAINLESS STEEL RIM | |
| | 2XT 959 680-637 | SATIN CHROME PLATED STAINLESS STEEL RIM | |




| | Clear Lens | |
|-----|-----------------|---|
| | 2XT 959 680-707 | LAMP ONLY |
| RED | 2XT 959 680-717 | POLISHED STAINLESS STEEL RIM |
| | 2XT 959 680-727 | GOLD PLATED STAINLESS STEEL RIM |
| | 2XT 959 680-737 | SATIN CHROME PLATED STAINLESS STEEL RIM |



Low Profile - Step Courtesy Lamp

Flush mount step lamp with either white, blue, amber or red LEDs, and a selection of cover colours.











| LOW PROFILE - STEP COURTESY LAMP | | | |
|---|--|--|--|
| Mounting | Single hole recess mount (foam gasket supplied). | | |
| Voltage | Multivolt for optimum brightness in 12 and 24 volt systems. | | |
| Power Consumption | Consumption 0.5W | | |
| Protection | Reverse polarity protection. Fully sealed against dust, high-pressure washing and temporary water immersion. | | |
| Cable Length Pre-wired with 100mm of cable. | | | |
| Pack Size | 20 lamps | | |
| Approval Markings | (€ | | |
| Lamp covers cannot be removed easily once clipped into place. | | | |



| WHITE | Clear Lens | |
|-------|-----------------|-------------------------|
| | 2JA 998 560-127 | SATIN CHROME PLATED CAP |
| | 2JA 998 560-007 | CHROME PLATED CAP |
| | 2JA 998 560-087 | GOLD PLATED CAP |
| | 2JA 998 560-017 | WHITE CAP |
| | 2JA 998 560-117 | BLACK CAP |



| | Clear Lens | |
|---|-----------------|-------------------------|
| | 2JA 998 560-107 | SATIN CHROME PLATED CAP |
| 当 | 2JA 998 560-047 | CHROME PLATED CAP |
| 표 | 2JA 998 560-097 | GOLD PLATED CAP |
| | 2JA 998 560-057 | WHITE CAP |
| | 2JA 998 560-157 | BLACK CAP |



| AMBER | Clear Lens | |
|-------|-----------------|-------------------------|
| | 2JA 998 560-347 | SATIN CHROME PLATED CAP |
| | 2JA 998 560-307 | CHROME PLATED CAP |
| | 2JA 998 560-337 | GOLD PLATED CAP |
| | 2JA 998 560-317 | WHITE CAP |
| | 2JA 998 560-327 | BLACK CAP |



| | Clear Lens | |
|---|-----------------|-------------------------|
| | 2JA 998 560-247 | SATIN CHROME PLATED CAP |
| | 2JA 998 560-207 | CHROME PLATED CAP |
| ~ | 2JA 998 560-237 | GOLD PLATED CAP |
| | 2JA 998 560-217 | WHITE CAP |
| | 2JA 998 560-227 | BLACK CAP |











DuraLED Surface Mount Courtesy Lamp

Amber, blue, red, white or green LED courtesy lamps with a diffusion lens.









2XT 959 630-457

2XT 959 630-357

2XT 959 630-257



2XT 959 630-557

| | l28.9l | | |
|-------------------|---|---|-------|
| | 2XT 959 630-457 | | WHITE |
| | 2XT 959 630-157 | | AMBER |
| Part Number | 2XT 959 630-357 | | RED |
| | 2XT 959 630-257 | | BLUE |
| | 2XT 959 630-557 | | GREEN |
| Mounting | Two hole surface mount. | | |
| Voltage | Multivolt for optimum brightness at input voltage from 8 to 28 volts (red and amber lamps), or between 10 and 33 volts (blue, white and green lamps). | | |
| Power Consumption | <1W | | |
| Protection | Reverse polarity and transient spike circuit protection. IP 6K6 (Protection against dust and high pressure water jets) IP 6K7 (Protection against dust and temporary water immersion) | | |
| Cable Length | Pre-wired with 0.5m of sheathed multi-core cable. | | |
| Pack Size | 16 lamps | | |
| Approval Markings | E4) 10R 04-2906 | (€ | |
| Spare Parts | 9BG 959 565-007 9BG 959 565-017 9BG 959 565-037 9BG 959 565-047 9BG 959 565-057 9BG 959 565-067 9BG 959 565-077 9BG 959 565-407 | Black shroud White shroud Red shroud Yellow shroud Green shroud Blue shroud Amber shroud Chrome plated shroud | |

Dimmable: Analog DC Input









| 132 | 60- |
|-----|---------|
| 38 | -28.9 - |

| Part Number | 2XT 959 630-107 | | AMBER |
|-------------------|---|--|-------|
| Part Number | 2XT 959 630-307 | | RED |
| Mounting | Two hole surface mount. | | |
| Voltage | 12V DC | | |
| Power Consumption | <1W | | |
| Protection | Reverse polarity and transient spike circuit protection. IP 6K6 (Protection against dust and high pressure water jets) IP 6K7 (Protection against dust and temporary water immersion) | | |
| Cable Length | Pre-wired with 150mm of cable. | | |
| Pack Size | 24 lamps | | |
| Spare Parts | 9BG 959 565-017 WI 9BG 959 565-037 Re 9BG 959 565-047 Yei 9BG 959 565-057 Gr 9BG 959 565-067 Blu 9BG 959 565-077 An | ack shroud hite shroud d shroud clow shroud een shroud ue shroud nber shroud rome plated shroud | |

DuraLED Surface Mount Courtesy Lamp

Amber or red LED courtesy lamps with a clear lens.





2XT 959 630-307