



Headlamps and Inserts

HELLA has manufactured headlamp systems for more than 100 years. The durability and reliability of HELLA products has made HELLA a world leader in headlamp technology.




Contents

Headlamps and Inserts


90mm Bi-LED Headlamps.....	104
90mm Bi-Halogen Headlamps.....	105
90mm LED Headlamps.....	106
90mm LED Fog Lamps.....	107
90mm Universal Headlamps.....	108-109
7" Round LED Headlamps.....	110-111
7" Round Headlamps.....	112-113
5 ¾" Round Headlamps.....	114-115
Rectangular Headlamps & Housings.....	116-117
DAF/Scania HeadLamps.....	118
BMW/139mmØ HeadLamps.....	119
Universal Headlamps.....	120
Headlamp Accessories.....	121

Bi-LED 90mm 2nd Generation High/Low Beam Headlamp

LED high/low beam headlamp featuring a generous spread of light and strong high beam for the open road. Low power consumption and ultra long life equates to economical running costs compared to a bulb lamp. Exceptional white light output and extremely homogeneous illumination for reduced driver eye strain which means greater safety. Complete with 4 screw adjusters and DT plug.




Part Number	1032-G2	
Mounting	3 point mount, screw adjusters included.	
Voltage	Multivolt™ for optimum brightness in 12 and 24 volt systems.	
Power Consumption	High beam:	30W
	Low beam:	20W
Protection	IP 6K4K (Protection against dust and high-pressure water splash) IP 6K9K (Protection against dust and high-pressure/steam jet cleaning)	
Connection	4 pole DT socket	
Spare Parts	4962-P 9.1029.12	4 pole DT plug kit (included) Mounting frame
Compliance	(E) 4209 Ref. 12.5 ECE R112/01	




P/N 9.1029.12

P/N 1032-G2 High Beam distance. (m)




HEADLAMPS AND INSERTS

**Bi-Halogen 90mm H7 High/Low Beam Headlamp**


Compact H7 Low/High Beam headlamp. Pattern-free hardened glass lens and Free-Form (FF) cast aluminium reflector. Excellent light output and extremely homogeneous illumination with virtually no scatter. Straight-forward installation with 3 pre-mounted adjustment screws on the vehicle body. Matching connectors included.

Part Number	1LL 009 998-011		12 VOLT
	1LL 009 998-051		24 VOLT
Bulbs to Suit	12V 24V	CA1255 CA2470	
Spare Parts	9.1029.11 9.1534.05	Mounting frame Bulb connector	
Compliance	(E) 2484		



P/N 9.1029.11

P/N 9.1534.05

**High Beam distance. (m)****Headlamp Adjusters**

Adjuster to suit 90mm headlamps.

Part Number	15297700		PACK OF 3
	25416300		PACK OF 3
To Suit	P/N 15297700 P/N 25416300	Suits 14mm Ø mounting holes Suits 17mm Ø mounting holes	




P/N 15297700



P/N 25416300

LED 90mm Low Beam

LED low beam featuring a generous spread of light. Low power consumption and ultra long life equates to economical running costs compared to a bulb lamp. Exceptional white light output and extremely homogeneous illumination for reduced driver strain which means greater safety. Complete with 3 screw adjusters.




Part Number	1ML 012 488-011	
Mounting	3 point mount, screw adjusters included.	
Voltage	Multivolt™ for optimum brightness in 12 and 24 volt systems.	
Power Consumption	20W	
Protection	IP 5K4K (Protection against dust and high-pressure water splash) IP 5K9K (Protection against dust and high-pressure/steam jet cleaning)	
Connector	4 Pole FEP socket (Plug not included)	
Spare Parts	25416300 9.1029.11 4988-P 4988-DT	Adjusters (3, included) Mounting frame (not included) 4 pole FEP plug kit 4 pole FEP to DT adaptor
Compliance	(E) 4090	ECE R112/01



LED 90mm High Beam


LED high beam featuring a generous spread of light. Low power consumption and ultra long life equates to economical running costs compared to a bulb lamp. Exceptional white light output and extremely homogeneous illumination for reduced driver strain which means greater safety. Complete with 3 screw adjusters.




Part Number	1F0 011 988-121	
Mounting	3 point mount, screw adjusters included.	
Voltage	Multivolt™ for optimum brightness in 12 and 24 volt systems.	
Power Consumption	20W	
Protection	IP 5K4K (Protection against dust and high-pressure water splash) IP 5K9K (Protection against dust and high-pressure/steam jet cleaning)	
Connector	4 Pole FEP socket (Plug not included)	
Spare Parts	25416300 9.1029.11 4988-P 4988-DT	Adjusters (3, included) Mounting frame (not included) 4 pole FEP plug kit 4 pole FEP to DT adaptor
Compliance	(E) 3831 Ref. 12.5	ECE R112/01



LED 90mm High Beam distance. (m)





Part Number	1N0 011 988-001		
	1N0 011 988-011 (Daytime Running Lamp/Front Position)		
Voltage	Multivolt™ for optimum brightness in 12 and 24 volt systems.		
Power Consumption	Fog:	25W	
	Daytime Running Lamp:	15W (1N0 011 988-011 version only)	
	Front Position:	3W (1N0 011 988-011 version only)	
Protection	IP 5K4K (Protection against dust and high-pressure water splash) IP 5K9K (Protection against dust and high-pressure/steam jet cleaning)		
Connector	4 Pole FEP socket (Plug not included)		
Spare Parts	4988-P	4 pole FEP plug kit	
	4988-DT	4 pole FEP to DT adaptor	
Compliance	Fog:	Ⓔ 3831	ECE R19/03
	Daytime Running Lamp:	ECE R87/00	
	Front Position:	ECE R7/02	

LED 90mm Fog Lamp

LED Fog lamp featuring a generous spread of light. Low power consumption and ultra long life equates to economical running costs compared to a bulb lamp. Exceptional white light output and extremely homogeneous illumination for reduced driver strain which means greater safety.



P/N 1N0 011 988-011 LAMP FUNCTIONS




Daytime running lamp

Front position

Part Number	9.1029.09 (Mounting frame)	
	9.1029.10 (Mounting frame)	
	9.1029.11 (Mounting frame)	
	9.1029.12 (Mounting frame)	
	4988-P (4 pole FEP plug kit)	
	4988-DT (4 pole FEP to DT adaptor)	
To Suit	P/N 4988-P P/N 4988-DT P/N 9.1029.09 P/N 9.1029.10 P/N 9.1029.11 P/N 9.1029.12	P/Ns 1ML 012 488-011/1F0 011 988-12 / 1N0 011 988-001/...-011 P/Ns 1ML 012 488-011/1F0 011 988-12 / 1N0 011 988-001/...-011 P/Ns 1029-24V and 1030-24V P/Ns 1029H1-24V and 1030H1-24V P/Ns 1ML 012 488-011/1F0 011 988-121 P/Ns 1032-G2

90mm Headlamp Plugs, Adaptors and Mounting Frames

Spare parts to suit 90mm headlamps




P/N 9.1029.09

P/N 9.1029.10



P/N 4988-P




P/N 4988-DT

P/N 9.1029.12

P/N 9.1029.11

H7 Headlamp - 24 Volt

Compact H7 headlamps with glass lens for buses, coaches and mobile homes. Includes headlamp adjusters.



Part Number	1029-24V	LOW BEAM
	1030-24V	HIGH BEAM
Bulbs to Suit	Low/High Beam:	12V CA1255
	Position:	24V CA2470
		HL124 HL244
Spare Parts	15297700	Headlamp adjuster (Pack of 3)
	9GH 152 654-007	Rear cap
	8JD 156 150-807	Two pole plug with terminals and seals for position lamp
	9.1029.09	Mounting frame
Compliance	(E1) 917	



P/N 1030-24V




P/N 15297700



P/N 9GH 152 654-007




P/N 8JD 156 150-807



P/N 9.1029.09

P/N 1030-24V High Beam distance. (m)



HEADLAMPS AND INSERTS

<div><div><div>Certified</div><div>ECE</div><div>CERTIFIED</div></div><div><div>Bulb Included</div><div>24V</div><div>BULB INC</div></div></div> <div><div><div><div>85</div><div>114</div><div>85</div></div><div><div>160</div><div>92</div><div>90</div></div></div><div><div><div>113</div><div>85</div><div>85</div></div><div><div>96</div><div>113</div><div>90</div></div></div><div><div>P/N 1029H1-24V</div><div>P/N 1030H1-24V</div></div></div>			
Part Number	1029H1-24V		LOW BEAM
	1030H1-24V		HIGH BEAM
Bulbs to Suit	Low/High Beam:	12V C1255	24V C2470
	Position:	HL124	HL244
Spare Parts	25416300	Headlamp adjuster (Pack of 3)	
	9GH 152 654-007	Rear cap	
	8JD 156 150-807	Two pole plug with terminals and seals for position lamp	
	9.1029.10	Mounting frame	
Compliance	(E) 2397		

H1 Headlamp - 24 Volt

H1 headlamps with die cast aluminium reflector and hardened glass lens.




P/N 9.1029.10	P/N 8JD 156 150-807	P/N 9GH 152 654-007	P/N 25416300



P/N 1030H1-24V


P/N 1030H1-24V High Beam distance. (m)










7" Round LED Headlamps - High/Low Beam and Daytime Running Lamp/Front Position

The high/low beam function of the 7" LED headlamp range offers 1150/750 lumen light output and a wide spread creating a superior light distribution increasing peripheral vision. With the added feature of Daytime Running Lamps and Front Position Lamps the 1058LED is a one-stop-shop for all headlight needs, increasing visibility and therefore safety on the road.

Combining the latest state of the art LED technology, multivoltage 12/24V DC circuit design and precision optics, the retrofit lamps provide outstanding visibility, safety, and durability – making them one of the most advanced 7" LED headlamps available. The tough die-cast aluminium housing is IP 67 sealed against water and dust ingress with a UV resistant, hard coated polycarbonate lens making the HELLA's 7" Round LED Headlamp range perfect for use on and off-road.



Part Number	1056LED				
Mounting	Retrofit 178 Ø (7") headlamps				
Voltage	Multivolt™ for optimum brightness in 12 and 24 volt systems.				
Power Consumption	High Beam:	35W			
	Low Beam:	25W			
Light Output	High Beam:	1150 lumen			
	Low Beam:	750 lumen			
Protection	Reverse polarity protection. IP 67 (Protection against dust and high pressure water jets)				
Connection	3 PIN "H4" type male plug (100mm cable)				
Housing Material	Die-cast Aluminum				
Lens Material	Coated polycarbonate				
Compliance	ECE R112/01	Ref. 12.5		7581	
Part Number	1058LED (Daytime Running Lamp/Front Position)				
Power Consumption	High Beam:	35W			
	Low Beam:	25W			
	Daytime Running Lamp:	15W (1058LED version only)			
	Front Position:	2W (1058LED version only)			
Cable Length	P/N 1058LED has 2 additional 100mm pre-wired cables with male blade terminals for front position and daytime running lamp functions.				
Compliance	ECE R112/01	Ref. 12.5		6081	ECE R87/00 ECE R7/02 
Other specifications as per P/N 1056LED					



P/N 1056LED




P/N 1058LED

P/N 1058LED LAMP FUNCTIONS





Daytime Running Lamp Front position

1056LED/1058LED High Beam distance. (m)




1056LED/1058LED Low Beam distance. (m)





Part Number	1358LED
Mounting	Retrofit 178 Ø (7") headlamps
Voltage	Multivolt™ for optimum brightness in 12 and 24 volt systems.
Power Consumption	60W
Light Output	1440 lumen
Operating Temperature	-40°C to 65°C
Protection	Reverse polarity protection. IP 67 (Protection against dust and high pressure water jets)
Cable Length	2 x 100mm cables with male blade terminals.
Housing Material	Die-cast Aluminum
Lens Material	Coated polycarbonate
Compliance	E4 7501 ECE R112/01 Ref. 30

1358LED High Beam distance. (m)



7" ROUND LED HEADLAMPS


7" Round LED Headlamp - High Beam

The 1358LED lamp features a high beam function with a massive 1440 lumen light output for only 60W. Combining the latest state of the art LED technology, multivoltage 12/24V DC circuit design and precision optics, the retrofit lamps provide outstanding visibility, safety, and durability – making them one of the most advanced 7" LED headlamps available. The tough die-cast aluminium housing is IP67 sealed against water and dust ingress with a UV resistant, hard coated polycarbonate lens making the HELLA's 7" Round LED Headlamp range perfect for use on and off-road.



7" (178mm) Headlamp Housing

Headlamp housing and chrome rim for halogen or sealed beams and inserts 7" (178mm) in diameter. Fully sealed steel cowl, complete with adjusting mechanism for vertical and horizontal alignment, sealing gasket, stainless steel retaining rim and 3 pin wiring harness with separate park lamp connection. Ideal for truck, bus or body builders. Suits Mercedes, Kenworth, Mack, White etc. Outer chrome rim (P/N 1017) to suit headlamp housing P/N 1016.



Part Number	1016	HEADLAMP HOUSING
	1017	CHROME RIM




P/N 1016
Headlamp housing

P/N 1017
Chrome rim


7" (178mm) H4 Halogen High/Low Beam Insert

Semi-sealed headlamp with sealing cap.



Part Number	1056		
Bulbs to Suit	Headlamp:	12V	24V
		XD1260/55	XD2475/70
Compliance	E4 53		

Where front position lamp is required, use P/N 1058.




Rear view

7" (178mm) H4 Halogen High/Low Beam Insert

Semi-sealed headlamp with front position lamp bulb holder (includes P/N HL124 bulb) and sealing boot.



Part Number	1058		
Bulbs to Suit	Headlamp:	12V	24V
		XD1260/55	XD2475/70
		Front position: HL124	HL244
Compliance	E4 53		




Rear view

7" (178mm) H4 Halogen High/Low Beam Insert - Hardened Glass

High performance Halogen headlamp insert fitted with extremely robust hardened glass lens providing maximum resistance when subjected to high operating temperatures and thermal shock. Ideal for 24 volt and high wattage bulb applications. Supplied complete with sealing boot and front position lamp bulb holder assembly.




Part Number	1058HD		
Bulbs to Suit	Headlamp:	12V	24V
		XD1260/55	XD2475/70
		Front position: HL124	HL244
Compliance	E4 53		



Rear view




Part Number	9.1358.01	
Bulbs to Suit	12V	YC1255
	24V	YC2470
Compliance	E1 14529	



7" (178mm) H3 Halogen Driving Lamp Insert

Suitable for use as high beam headlamp in most 178mm round headlamp carriers (eg. P/N 1016).



Part Number	1016	HEADLAMP HOUSING
	1017	CHROME RIM

7" (178mm) Headlamp Housing

Headlamp housing and chrome rim for halogen or sealed beams and inserts 7" (178mm) in diameter. Fully sealed steel cowl, complete with adjusting mechanism for vertical and horizontal alignment, sealing gasket, stainless steel retaining rim and 3 pin wiring harness with separate park lamp connection. Ideal for truck, bus or body builders. Suits Mercedes, Kenworth, Mack, White etc. Outer chrome rim (P/N 1017) to suit headlamp housing P/N 1016.




P/N 1016
Headlamp housing

P/N 1017
Chrome rim

5 ¾" (146mm) H4 Halogen High/Low Beam Insert

Semi-sealed headlamp with front position lamp bulb holder (includes P/N HL124 bulb) and sealing boot. Suitable for dual headlamp systems.



Part Number	1055		
Bulbs to Suit		12V	24V
	Headlamp:	XD1260/55	XD2475/70
	Front position:	HL124	HL244
Spare Parts	13839700	Front position bulb holder	
	9GH 126 647-011	Sealing boot	
Compliance	(E1) 17031		



Rear view

Sealing boot

5 ¾" (146mm) H4 Halogen High/Low Beam Insert - Hardened Glass

High performance Halogen headlamp insert fitted with extremely robust hardened glass lens, providing maximum resistance when subjected to high operating temperatures and thermal shock. Ideal for 24 volt and high wattage bulb applications. Supplied complete with sealing boot and front position lamp bulb holder assembly.



Part Number	1055HD		
Bulbs to Suit	Headlamp:	12V	24V
	Front position:	XD1260/55 HL124	XD2475/70 HL244
Compliance	E1 17031		



Rear view

5 ¾" (146mm) H1 Halogen Low Beam Insert


Low beam insert with front position lamp bulb holder and sealing boot. Suitable for dual headlamp systems.



Part Number	1054		
Bulbs to Suit		12V	24V
	Headlamp:	C1255	C2470
	Front position:	HL124	HL244
Spare Part	9GH 113 763-001	Sealing boot	
Compliance	(E1) 7076		



Rear view



Part Number	1053		
Bulbs to Suit	Headlamp:	12V C1255	24V C2470
Spare Part	9GH 113 763-001	Sealing boot	
Compliance	(E1) 14464		
Earth terminal is a 'Post' (bullet) type connection.			



Rear view

Sealing boot



5 3/4" (146mm) H1 Halogen
Long Range Driving Insert

Semi-sealed headlamp, for high beam section of dual headlamp systems and sealing boot.

Part Number	1040		
Bulbs to Suit	Headlamp:	12V	24V
		C1255	C2470
Spare Part	9GH 113 763-001	Sealing boot	




Rear view

Sealing boot

165 x 100mm H4 Halogen High/Low Beam Insert

Semi-sealed headlamp and front position lamp
with sealing boot.



Part Number	1044		
Bulbs to Suit		12V	24V
	Headlamp:	XD1260/55	XD2475/70
	Front position:	HL124	HL244
Spare Part	9FF 126 444-001	Front position bulb holder	
Compliance	Ⓔ 7197		



Rear view

165 x 100mm H4 Halogen High/Low Beam Insert

Semi-sealed headlamp with sealing boot
and wiring adaptor.



Part Number	1042		
Bulbs to Suit	Headlamp:	12V XD1260/55	24V XD2475/70
Spare Part	9GH 126 647-011	Sealing boot	
Compliance	(E) 7197		



Rear view



Sealing boot

165 x 100mm H1 Halogen High Beam Insert

Semi-sealed headlamp with sealing cap.



Part Number	1041		
Bulbs to Suit	Headlamp:	12V	24V
		C1255	C2470
Compliance	(E1) 24504		



Rear view



Part Number	1043		
Bulbs to Suit	Headlamp:	12V	24V
	Front position:	XD1260/55 HL124	XD2475/70 HL244
Spare Parts	13839700 96H 126 647-011	Front position bulb holder Sealing boot	
Compliance	(E1) 17009	(E1) 17119	




Rear view

Sealing boot

200 x 142mm H4 Halogen High/Low Beam Insert

Semi-sealed headlamp with front position lamp bulb holder (includes P/N HL124 bulb).




Rectangular Headlamp Housing

Suits 200 x 142mm rectangular headlamp units (P/N 1043). Ideal for truck, bus or body builders.



Part Number	1024
-------------	------



Twin Rectangular Headlamp Housing

For most 165 x 100mm rectangular headlamp units. Chrome plated outer rim. Complete with adjusting mechanisms for vertical/horizontal alignment and wiring loom. Ideal for truck, bus or body builders.



Part Number	1025	
Spare Part	9.1025.07	Chrome plated outer rim

DAF Headlamp. CF65/75/85
LF45/55, XF95/105 01/01-05-13



Part Number	HEADLAMP (H1/H7)	
	1LJ 247 046-071	LH
	1LJ 247 046-081	RH
Bulbs to Suit	Low Beam: CA2470 High Beam: C2470	
Compliance	E1 1134	

Scania Headlamp, P94 - T164
(series 4) 95-04, P230 - T470 04-on




Part Number	HEADLAMP (H4)	
	1LG 007 150-111	LH
	1LG 007 150-121	RH
Bulbs to Suit	Headlamp: XD2475/70 Indicator: R2421 Position: G2410	
Spare Parts	9ES 144 433-031 Lens, left 9ES 144 434-031 Lens, right 9EL 145 103-011 Lens for indicator - left 9EL 145 104-011 Lens for indicator - right	
Compliance	E1 111	E4 276

5-Series (E39) 09/00 - 06/04



Part Number	HEADLAMP (H7/H7) WITH ELECTRIC LEVELLER	
	1LL 008 053-591	LH
	1LL 008 053-601	RH
Bulbs to Suit	Headlamp: CA1255 x 2 Indicator: RY1221 Position: YL1210	
Spare Part	9DX 153 746-011	Position lamp bulb holder
Compliance	(E1) 1182	



Part Number	1L3 996 002-221		
	1L3 996 002-411 (with Front Position)		
Bulbs to Suit	Headlamp: XD1260/55 Front Position: HL124	12V XD2475/70 HL244	24V XD2475/70 HL244
Compliance	(E12) 20005		

139mmØ H4 headlamp with Frame




P/N 1L3 996 002-221



P/N 1L3 996 002-411

LED Combination Headlamp - High/Low Beam and Indicator/ Position


Combination headlamp with all functions in LED technology. For horizontal mounting, with die-cast aluminum housing, lens made of scratch-resistant polycarbonate, with 6-pin DEUTSCH connector, light functions: low and high beam, position light and indicator.



Part Number	1LE 996 374-031	LEFT HAND
	1LE 996 374-041	RIGHT HAND
Mounting	Single bolt mount, upright.	
Voltage	Multivolt™ for optimum brightness in 12 and 24 volt systems.	
Power Consumption	High beam 40W Low beam 25W Indicator 8W Position 1W	
Protection	IP 6K4K (Protection against dust and water splash) IP X9K (Protection against high-pressure jets)	
Connection	6 pole DT socket	
Spare Parts	4963-P 6 pole DT plug, wedge and 6 contacts	
Compliance	(E1) 4079 ECE R112/01 Ref. 12.5 ECE R6/01 ECE R7/02	


H4 Halogen High/Low Beam Headlamp Assembly

Lamp unit, lens dimensions 352 x 195mm, complete with mounting frame and adjusting mechanisms for vertical and horizontal alignment. Fully enclosed housing with removable rear sealing cap for bulb replacement access. Ideal for truck, bus or body builders.



Part Number	1027		
Mounting	Simple four point mounting.		
Bulbs to Suit		12V	24V
	Headlamp:	XD1260/55	XD2475/70
	Front position:	HL124	HL244
Spare Parts	9.1027.01	Clear lens	
	9.1027.02	Reflector	
	9.1027.04	Sealing cap	
Compliance	Ⓔ 17016		

External Headlamp



Part Number	HEADLAMP (H7/H3)	
	1LA 993 975-071	LH
	1LA 993 975-081	RH
Bulbs to Suit	Dipped Beam: CA2470 Main Beam: YC2470 Indicator: R2421 Position: HL244	
Protection	IP X9K (Protection against high pressure steam/jet cleaning)	
Spare Parts	1LA 990 185-011 Light unit 9EL 990 186-001 Lens for indicator lamp, front 9EL 990 186-101 Lens for indicator lamp, rear	
Accessories	8JD 008 151-051 Socket for AMP plug connector	
Compliance	(E4) 9496	




8JD 008 151-051

Part Number	4972-H1	H1
	4972-H4	H4
	4972-H7	H7

Bulb Connectors

Plug with pre-installed leads and crimp connectors (H1 and H7). Adapts to original wiring by crimp connector and heat shrink insulator, H4 version with 200mm leads (no connectors).



P/N 4972-H7

P/N 4972-H1

HID Gas Discharge (G3) Power Pack

Part Number	5DV 007 760-631	12 VOLT
	5DV 007 810-171	24 VOLT
To Suit	Bulb P/Ns D2S and D2R.	



HID Gas Discharge (G4) Power Pack

Part Number	5DV 008 855-001	12 VOLT
	5DV 008 856-001	24 VOLT
To Suit	Bulb P/Ns D1S and D1R.	



HID Gas Discharge Ignitor

Part Number	5DD 008 319-501	12/24 VOLT
To Suit	Bulb P/Ns D2S and D2R	

