

959 149-28 / 06.20



INSTRUCTION SHEET for: 2BA 959 075-xxx / 2156-12V & 2156-24V



Lamp Mounting Instructions

Determine mounting position and holes per diagram overleaf. (Before fitment see Wiring Colour Coding below)

Ensure gasket is fitted to lamp to provide a weather tight seal. Fit lamp to mounting aperture with the screws provided.

Fit screw caps.

Note: Do not overtighten mounting screws in lens. If it is necessary to remove the screw caps, use a pin.

Wiring Colour Coding

Note: Lamp is polarity conscious. The reversal of the polarity will not damage this product but will inhibit its function.

Wire Colour	Connect to	Power Consumption
Amber	Positive	Less than 2 watts
Black	Negative	-

NB: Lamp must be protected by a fuse rated at 2 amperes maximum.

Compatibility to existing electrical systems

It is important for the installer to ascertain the compatibility of the low power consumption LED lamps with the electrical and/or electronic systems of the complete vehicle, including trailers. In most cases the reduced power consumption is beneficial by imposing less demands on the entire electrical system.

For certain functions some electrical systems rely on a set power consumption for monitoring whether, for example, an indicator globe has failed or a trailer is connected.

Operation of this lamp using alternating current or modulated direct voltage will cause premature light failure. HELLA recommends connecting ADR or ECE certified LED signal and marker lamps to a continuous (unmodulated) 12V or 24V power supply to ensure safe light operation.

Warranty Statement

Congratulations! The product you have selected comes from Hella - one of the world's leading manufacturers of automotive and marine products.

Hella branded products are covered by a warranty against manufacturing or material defects. (For further details check Hella's terms of trade with your dealer).

The lamp is sealed and does not have any serviceable parts inside; opening the lamp will invalidate warranty.

In the unlikely event that you should experience a problem with this product, please contact your Hella dealer where you purchased the product.



Lamp Mounting Instructions

Determine mounting position and holes per diagram overleaf. (Before fitment see Wiring Colour Coding below)

Ensure gasket is fitted to lamp to provide a weather tight seal. Fit lamp to mounting aperture with the screws provided.

Fit screw caps.

Note: Do not overtighten mounting screws in lens. If it is necessary to remove the screw caps, use a pin.

Wiring Colour Coding

Note: Lamp is polarity conscious. The reversal of the polarity will not damage this product but will inhibit its function.

Wire Colour	Connect to	Power Consumption
Amber	Positive	Less than 2 watts
Black	Negative	-

NB: Lamp must be protected by a fuse rated at 2 amperes maximum.

Compatibility to existing electrical systems

It is important for the installer to ascertain the compatibility of the low power consumption LED lamps with the electrical and/or electronic systems of the complete vehicle, including trailers. In most cases the reduced power consumption is beneficial by imposing less demands on the entire electrical system.

For certain functions some electrical systems rely on a set power consumption for monitoring whether, for example, an indicator globe has failed or a trailer is connected.

Operation of this lamp using alternating current or modulated direct voltage will cause premature light failure. HELLA recommends connecting ADR or ECE certified LED signal and marker lamps to a continuous (unmodulated) 12V or 24V power supply to ensure safe light operation.

Warranty Statement

Congratulations! The product you have selected comes from Hella - one of the world's leading manufacturers of automotive and marine products.

Hella branded products are covered by a warranty against manufacturing or material defects. (For further details check Hella's terms of trade with your dealer).

The lamp is sealed and does not have any serviceable parts inside; opening the lamp will invalidate warranty.

In the unlikely event that you should experience a problem with this product, please contact your Hella dealer where you purchased the product.

